


Fluted grip knob with threaded pin



Code	Description	Dimensions				Insert		Weight grams	Stock
		D	L	d1	l2	d	l		
01200C1A10	200C1/15 M4x10	15	12	11	1,5	M4	10	4	✓
01200C2B10	200C2/15 M5x10	15	12	11	1,5	M5	10	5	✓
01200C2B20	200C2/15 M5x20	15	12	11	1,5	M5	20	6	✓
01200C3B13	200C3/18 M5x13	18	17	12	4	M5	13	8	✓
01200C4C13	200C4/18 M6x13	18	17	12	4	M6	13	10	✓
01200C5B40	200C5/24 M5x40	24	17	16	5,5	M5	40	14	✓
01200C5C15	200C5/24 M6x15	24	17	16	5,5	M6	15	14	✓
01200C5C40	200C5/24 M6x40	24	17	16	5,5	M6	40	16	✓
01200C6D15	200C6/24 M8x15	24	17	16	5,5	M8	15	18	✓
01200C6D25	200C6/24 M8x25	24	17	16	5,5	M8	25	20	✓

Material

High resistance phenolyc-based (PF) duroplast. Resistant to organic and inorganic chemical substances such as oils, greases, fuels and solvents.

Colour

Black with shiny finish.

Insert

Galvanized steel.

Package

25 - 50 - 100 pcs.

